





## Combined Rope Track |



**Combined Rope Track**

Combined Rope Track, all units are suitable for children of 2 years, and include the necessary clips which can be fixed as needed. The posts designed for concreting are manufactured of hot-dip galvanized steel Ø 102 mm, (supply with red varnish for self-painting), and are 2 m long with red caps. The Herkules rope used for all ropes, climbing nets and hanging ladders include 6 steel strands enclosed by polyester jackets for high colour fastness and exceptionally good abrasion-resistance.

**Order No. 300000**

**Safety Advice:**

- Item height: 1.30 m
- Height of fall: 1.00 m
- Required space and safety zone resp. fall protection each vary according to combination resp. each per type of individual item.
- Subgrade: Up to a height of fall of 1.50 m grass as a subsoil is sufficient \*according to german safety requirements\*. For a height of fall exceeding 1.50 m, according to DIN EN1177 woodchips, bark mulch, sand or gravel is required.



**Climbing Net**

**Order No. 300010**



**Wiggle Beam**

**Order No. 300020**

\*Subject to technical alterations



**Splits Ropes**

Order No. 300030



**Hanging Ladder**

Order No. 300040



**Arched Rope**

Order No. 300050



**Tyres**

Order No. 300060



**Rubber Hammock**

Order No. 300070



**Suspended Rungs**

Order No. 300080

\*Subject to technical alterations



